CARINA RANGE

- IP44 3 Sided Porch Lanterns



PLLED3PIRBN

LED 3 Sided

Porch Lantern

with PIR

5012739

645433

Polycarbonate

Black base with

Clear Diffuser

H362 x W175 x

D100mm

550lms

700g

120°

0.6 - 1.5 m/s

8M±2M

40 seconds

PLLED3BN

LED 3 Sided

Porch Lantern

5012739

645426

Polycarbonate Black

base with

Clear Diffuser

H362 x W175 x

D100mm

550lms

650g

220/230V AC ~ 50/60Hz

IP44

80

LED non-replaceable

4,000K

-20°C to +35°C

7W

0.5 - 3.5M

30,000 hours

3 Years

BS EN 60598-2-1

Description

Barcode

Voltage

IP ratina CRI

Dimensions

Lamp Type

Class Type

Colour Temp

Operating Temp

Fitting Lumens

Max Wattage

PIR Detection

Angle

Speed

Detection Distance

Life Span

Guarantee

Conforms To

Duration Time

Product Weight

Installation Height

Detection Motion

Product Material

- Low energy alternative to standard wall lanterns
- Instant Illumination

Rust proof rugged polycarbonate

Available with or without PIR

Traditional design






For Outdoor Applications Only.

These products contains a light source of energy efficiency class F. The fittings are not dimmable.

> Total lumens of light source = 740 lm at 360°



(LED Only) light source by professional



The light source contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar aualified person.

CDEEN
BROOK

Tel: 01279 772 772 Fax: 01279 422 007

Email: sales@greenbrook.co.uk

PLLED3PIRBN

www.greenbrook.co.uk