

DELTA RANGE - IP20 LED Battens

Emergency Fittings

- + IP20
- + Steel body construction, Opal polycarbonate diffusers
- + Integrated driver
- + High output options in the same footprint
- + High LED chip efficiency
- + Compact design

Emergency Fittings
Greater than 3 hours emergency operation

TECHNICAL DATA SHEET



	LEDBAT5EM	LEDBAT6EM	LEDBAT5HEM	LEDBAT6HEM
Description	5ft Emergency Batten	6ft Emergency Batten	5ft Emergency Batten (High Output)	6ft Emergency Batten (High Output)
Barcode	5012739647741	5012739647758	5012739647840	5012739647857
Wattage	24W	32W	48W	64W
Power Rating	220V/240V AC ~50Hz			
Colour Temperature	4,000K			
Class	1			
IP Rating	IP20			
Lamp Type	LED Non-replaceable			
Lumens	2400	4000	3400	5200
Beam Angle	120°			
Ballast Type	LED Driver			
Battery Type	Ni-Cd, 6V, 3,000mAh			
Emergency Duration	More than 3 hours			
Main Housing	Steel Body with Polycarbonate Diffuser			
Dimensions	L1485 x W53 x H64mm	L1758 x W53 x H64mm	L1485 x W53 x H64mm	L1758 x W53 x H64mm
Mounting Options	BESA mount or Screw fixings			
Knockouts	2 x 20mm at ends of fitting and 1 x 20mm at the back of fitting			
Weight (g)	1811g	2041g	1857.5g	2053g
Guarantee	3 Years			
Conforms To	BS EN60598			