20A Lighting Connectors -For 3 & 4 Core Flex


NORSLO

- Easy lock & release system
- Large terminals for easy access
- **Designed & manufactured by GreenBrook**


ConneKt




Female Socket Up to 3 x 2.5mm² flat twin & earth cables can be used.



Male Socket Up to 2.5mm² flexible 3 core cable can be used.





Note:

- These couplers are suitable for installation in NON-READILY accessible areas.
- This system is NOT a replacement for a domestic plug and socket outlet system.
- Installation couplers are intended for connection and disconnection without load.
- Any dangerous compatibility between different manufacturer installation coupler system is not automatically prevented by compliance with IEC EN 61535.



Both the connectors come in POS display box containing 50 connectors

Ideal for Emergency lighting




LCGN4P

Tel: 01279 772 772 Fax: 01279 422 007

Email: sales@greenbrook.co.uk www.areenbrook.co.uk


Female Socket

Up to 3 x 2.5mm² flat twin & earth cables can be used.



Male Socket Up to 1 x 2.5mm² flexible 4 core cable can be used.





	LUUNUF	LUUN4F
Description	3 Way Connector	4 Way Connector
Pack Qty	50	50
Barcode	5012739 641404	5012739 645754
Max Voltage	400V	
Product Finish	Polycarbonate Enclosure, Nylon Connector	
Product Weight	55g	79g
Dimensions L x W x H	L 110 x W42 x H22.3mm	L 113 x W55 x H22.5mm
Guarantee	1 Year	
Conforms To	EN 61535	

Rev3-08.12.22