


FEATURES

- ▶ Can be used for long term projects in all weather conditions
- ▶ Weatherproof to IP66
- ▶ 1 or 2 hour 'Boost' & 'Advance' controls
- ▶ Ideal for control of: outdoor lighting, ponds, sprinkler systems
- ▶ 4 On & 4 Off settings per day, 700 hours battery back up
- ▶ Easy set - Day / 5 Day / 7 Day blocks



PSPTIG



TECHNICAL INFO

Product	PSPTIG
Description	Weatherproof Fused Connection Unit
Product Finish	Grey
Voltage	13A, 230V~240V 50Hz
Barcode	5012739644023
IP Rating	IP66
Display	Large Backlit Display
Rated Impulse Voltage	4,000V
Operation	Integrated Control
Max Load	Resistive - 13A Inductive - 6A
Manual Switch Type	Double Pole Switch
Timer Switch Type	Relay (Single Pole)
Cord Anchorage	Cable Dia:4.6mm to 10.4mm
Terminal Capacity	Cable Size: 3 x 1.0mm ² to 3 x 2.5mm
Knock Outs	20mm
Product Weight (nett)	502g
Packed Weight (gross)	578g
Product Dimensions	H137 x W132 x D80mm
Box Dimensions	H138 x W143 x D87mm
Guarantee	Timer 1 Year, Enclosure 5 Years
Timer Conforms to	BS1363-4, BS 5733:2010+A1:2014 BS EN 60730-1:2016+A1:2019 BS EN IEC 60730-2-7:2020
IP Box Conforms to	IEC 60670-1 & IEC 60670-22