



CB1/CB3



CB2/CB6



CB9

### FEATURES

- ▶ Black urea phenolic
- ▶ Easy knockout entries
- ▶ Lids can be sealed for security
- ▶ CB1/CB2/CB3 & CB6 conform to BS EN 60998-1 & BS EN 60998-2-1
- ▶ CB9 conforms to BS EN 60999-2

### TECHNICAL INFO

Product	CB1	CB3	CB2	CB6	CB9
<b>Description</b>	100A, 25mm <sup>2</sup>	100A, 35mm <sup>2</sup>	100A, 25mm <sup>2</sup>	100A, 35mm <sup>2</sup>	200A, 70mm <sup>2</sup>
<b>No of Ways</b>	5 Way	5 Way	2 x 5 Way	2 x 5 Way	6 Way
<b>Pack Qty</b>	20		10		1
<b>Barcode</b>	5012739 616808	5012739 616822	5012739 616815	5012739 616846	5012739 616853
<b>Colour</b>	Black Urea Phenolic				
<b>Power Rating</b>	230V AC ~ 50Hz				
<b>No of Poles</b>	Single	Single	Double	Double	Single
<b>Torque Setting</b>	2.5Nm Screw size M6	3.5Nm Screw size M8	2.5Nm Screw size M6	3.5Nm Screw size M8	3.5Nm Screw size M8
<b>Operating Temp</b>	-10°C - +40°C				
<b>Product Weight</b>	132g	188g	290g	493g	585g
<b>Dimensions H x W x D</b>	H64 x W47 x D38mm	H64 x W47 x D38mm	H89 x W65 x D55mm	H104 x W66 x D67mm	H125 x W64 x D55mm
<b>Guarantee</b>	1 Year				
<b>Conforms To</b>	BS EN 60998-1 & BS EN 60998-2-1				BS EN 60999-1 & BS EN 60999-2