

FEATURES

- ▶ Ideal use for Low Voltage lighting systems, junction boxes
- ▶ Can accept stranded, solid & flexible wires
- ▶ Re-usable

LEVER CONNECTORS -



TECHNICAL INFO

Product	LC2P	LC3P	LC5P	LC8P
Description	2 Pole Lever Connector	3 Pole Lever Connector	5 Pole Lever Connector	8 Pole Lever Connector
Pack Qty	100		50	
Barcode	5012739 649042	5012739 649059	5012739 649066	5012739 649073
Current	32A			
Voltage	250V			
Solid Conductor	0.8-2.5mm ²			
Stranded Conductor	0.8-2.5mm ²			
Striping Length	12mm			
Weight	2.5g	4g	7g	11g
Guarantee	1 Year			
Conforms to	EN 60998			

FEATURES

- ▶ Ideal use for Low Voltage lighting systems, junction boxes, consumer units
- ▶ Transparent casing for checking conductor is secure

PUSH-FIT CONNECTORS -



TECHNICAL INFO

Product	PFC2	PFC4	PFC6	PFC8
Description	2 Push-Fit Connector	4 Push-Fit Connector	6 Push-Fit Connector	8 Push-Fit Connector
Pack Qty	100			
Barcode	5012739 649080	5012739 649097	5012739 649103	5012739 649110
Current	24A			
Voltage	250V			
Solid Conductor	0.75-2.5mm ²			
Stranded Conductor	1.5-2.5mm ²			
Striping Length	12mm			
Weight	1g	2g	3g	3g
Guarantee	1 Year			
Conforms to	EN 60998			