



## FEATURES

- ▶ Ideal for control of:- towel rails, panel heaters, immersion heaters & fan heaters
- ▶ 4 'ON' & 4 'OFF' settings per day
- ▶ Large backlit LCD display
- ▶ 12mm pattress supplied if extra spacing is needed
- ▶ Fitted with front load replaceable 13A fuse
- ▶ Will fit 25-47mm back boxes
- ▶ '1 or 2 hour Boost' & 'Advance' controls
- ▶ 700 hour battery life
- ▶ Front cable entry
- ▶ 1 year guarantee

T205

Fused Timer Connection Unit

**Caution:** Regulation 433.1 of BS7671:2018 states:-

**'Every circuit shall be designed so that a small overload of long duration is unlikely to occur'.**

For loads exceeding 2.7kW in high ambient temperature environments (such as airing cupboards) the installer should consider installing a 20A double pole switch.

## TECHNICAL INFO

Product	T205
Description	Fused Timer Connection Unit 7 Day
Barcode	5012739653964
Max Load	13A Resistive Load 6A Inductive Load
Product Finish	White
Product Weight	188g
Product Dimensions	H86.5 x W86.5 x D40mm (D46.5mm including front switch)
Voltage	230V AC 50Hz
Rated Impulse Voltage	4,000V
Operating Temperature	-5°C to +40°C
Working Environment	Indoor use only
Operation	Integrated Control
Battery Back up	700 Hours
Display	Large Back Lit LCD
Pollution Degree	2
Manual Switch Type	Double Pole Switch
Timer Switch Type	Relay (single pole)
Settings	4 On & Off Settings per day
Cord Anchorage	Cable Dia: 4.6mm to 10.4mm
Terminal Capacity	Cable Size - 3 x 1.0mm <sup>2</sup> to 3 x 2.5mm <sup>2</sup>
Guarantee	1 Year
Conforms To	BS 5733:2010+A1:2014, BS EN60730-1:2016+A1:2019, BS EN IEC 60730-2-7:2020 Fused Connection Unit Tests to: BS 1363-4:2016+A1:2018