

FEATURES

- ▶ Automatically switches light fittings ON at dusk & OFF at dawn
- ▶ Ideal for external & communal lighting
- ▶ Switching delay 5-15 seconds
- ▶ Detachable sensing module
- ▶ Kit includes head, bracket, & fixing screws
- ▶ Replacement head available (code:PECH)



Note:

LED compatible can run loads of up to 500 watts, the total number of light fittings should be limited to no more than **10** fittings.

PEC1000 PHOTOCELL KIT



PECH PHOTOCELL REPLACEMENT HEAD

Important:

To extend the lifespan of the photocells, when wiring in series with a timer we recommend a volt free model such as the GreenBrook Din Rail Timer Model T80.

TECHNICAL INFO

Product	PEC1000	PECH
Description	Photocell Kit	Photocell Replacement Head
Barcode	5012739 622885	5012739 622977
Rated Voltage	110V - 240V	
IP Rating	IP65	
Light Level	On @ 5 Lux / Off @ 15 Lux	
Max Switching Capacity	10A	
Sensor Type	Photo-resistor	
Load Rating	Tungsten 1200W Inductive 2000VA LED 500W max (max 10 fittings)	
Operating Temp	- 40° - + 70°C	
Class Type	II	
Switching Delay	5 - 15 seconds	
Electrical Life	100,000 cycles	
Product Weight	156.5g	71.7g
Dimensions	ø78.5 x H125mm	ø78.5 x H50mm
Guarantee	1 Year	
Conforms to	EN IEC61058-1, EN61058-1-2, BS EN61058-1, BS EN61058-1-2 & BS EN IEC61547	