

FEATURES

- ▶ Ideal for most heating applications
- ▶ Timer 'ON' status indicator
- ▶ Fits 35mm dual appliance socket box, should you require the timer next to a fused spur or socket outlet
- ▶ Will fit directly to any 35mm deep socket box fitted with an earth terminal
- ▶ T108A is suitable for discharge lighting applications
- ▶ 1 Year Guarantee



T100A



T101A



T105A



T108A

TECHNICAL INFO

Product	T100A	T101A	T105A	T108A
Description	24 Hour Mechanical	7 Day Mechanical	7 Day Electronic	7 Day Electronic
Max Load	16A Resistive Load 2A Inductive Load			16A Resistive Load 8A Inductive Load
Product Finish	White			
Barcode	5012739 638671	5012739 638688	5012739 638695	5012739 638701
Product Weight	130g		150g	
Voltage	230V AC			
Ambient Temperature	-10°C to +55°C			
Shortest Switching Time	15 Minutes	2 Hours	1 Minute	
Battery Back Up	-	-	150 Hours	
Display	Mechanical - Analogue Clock Face	Mechanical - Analogue Clock Face & Minute Hand Indicator	Electronic - Digital Display	
Settings	96 On / Off, On/Timer/Off Switch Selector	84 On/Off, On/Timer/Off Switch Selector	24 On/Off, Summer Time Setting Option	24 On/Off, Summer Time Setting Option & Random Setting Option
Guarantee	1 Year			
Conforms To	BS EN 60730-1, BS EN 60730-2-7			

Please see overleaf for full Timer dimensions



T100A



T101A



T105A



T108A

