

New DRY LINING BOXES with pivoting lugs

TECHNICAL DATA SHEET

CORE SERIES



DL1N




DL2N



DL147N



DL247N



DLCN



DLDN

TECHNICAL INFO

Product Code	DL1N	DL2N	DL147N	DL247N	DLCN	DLDN
Description	1 Gang - 35mm Deep	2 Gang - 35mm Deep	1 Gang - 47mm Deep	2 Gang - 47mm Deep	1 Gang Circular - 32mm Deep	Dual Box - 35mm Deep
Pack Qty	10					
Max Wall/Plasterboard Thickness	Maximum dry lining depth: 28 mm (double plasterboard + skim finish)					
Product Finish	White Polycarbonate					
Barcode	5012739 644931	5012739 644948	5012739 644955	5012739 644962	5012739 644979	5012739 644986
Product Weight	47g	73g	57g	89g	37g	91g
K/O Dimensions	1 x ø25mm				2 x ø20mm	2 x ø25mm
Box Dimensions	73.5 x 73.5 mm	134 x 73.5 mm	73.5 x 73.5 mm	134 x 73.5 mm	66mm	158 x 73.5mm
Box Lip Dimensions	1.2mm					
Cable Entry Dimensions	2 x 16mm x 25mm				n/a	4 x 16mm x 26mm
Guarantee	1 Year					
Conforms To	BS 60670					

The Greenbrook dry lining lugs are designed to sit flush within the gap in the running bar.

- This keeps the threaded fixing hole central and consistent
- Ensures better alignment with the product's fixing holes

Benefits:

- Screws engage more easily without forcing alignment
- Accessory sits square on the first attempt, reducing adjustment time
- Minimizes risk of cross-threading or uneven tightening

Overall:

- Improves installation accuracy
- Delivers a cleaner, more professional finish with less effort