

Before Use:

- Read all instructions
- Work Platforms have a maximum load of 150Kg
- Keep the work platform clean - remove any paint, oil or dirt
- Inspect the work platform before first use - check operation of all parts and ensure it is safe to use at the start of each day
- Do not use a damaged work platform
- Before using the work platform at work, a risk assessment should be carried out
- For professional users, regular periodic inspection is required

Positioning the Work Platform:

- Work platforms should not be positioned on slippery surfaces (for example ice, shiny surfaces or on spillages) unless additional effective measures are taken to prevent the work platform slipping
- When positioning the work platform take into account risk of collision from people, vehicles, doors and windows. Secure doors (not fire exits) and windows where possible in the work area
- Work platforms should be positioned on an even level and unmoveable base with rungs or treads level and fully opened
- Work platforms should only be used on its feet in the upright position
- Identify any electrical risks in the work area, such as overhead lines or other exposed electrical equipment
- Locking devices, if fitted, should be fully secured before use
- Work platforms should never be repositioned from above

Using the Work Platform:

- Do not exceed the maximum total load for the type of work platform
- Do not overreach
- Avoid work that imposes a sideways load on, such as side-on drilling through solid materials (e.g. brick and concrete)
- Wear suitable footwear when climbing a work platform
- Face the work platform when ascending and descending
- Do not use the work platform for access to another level
- Use non-conductive work platform for unavoidable live electrical work
- Do not use the work platform as a bridge
- Equipment carried while using a work platform should be light and easy to handle
- Do not use the work platform outside in adverse weather conditions, such as strong wind
- Children should not use the work platform as a toy or without supervision
- Work platform should only be used for light work of short duration with regular breaks
- Care should be taken when opening and closing the legs

Storage:

The important considerations when storing a work platform (not in use) include the following:

- To avoid more rapid deterioration ensure the work platform is stored away from areas of dampness, excessive heat, or exposure to the elements
- The work platform should be stored in a position which helps it to remain straight (e.g. hung by the stiles on proper work platform brackets or laid on a flat clutter free surface)
- The work platform should be stored where it cannot be damaged by vehicles, heavy objects, or contaminants
- Ensure the work platform is stored where it cannot cause a trip hazard or an obstruction
- Ensure the work platform is secured against unauthorised usage (e.g. by children or criminals)

Repair:

These work platforms are not repairable, if damaged they should be disposed of.

Maintenance:

Refer to the 'Before Use' section of the instructions.

GUARANTEE
Your GreenBrook LADPF300 / LADPF600
is guaranteed for 1 year from the
date of purchase.
This is in addition to your statutory rights.

PLEASE KEEP THESE INSTRUCTIONS SAFE FOR FUTURE REFERENCE