

### FEATURES

- ▶ Type A RCD
- ▶ Mechanical flag trip indicators
- ▶ Mechanically latched - no need to reset after power loss
- ▶ All products have separate 'Test' & 'Reset' buttons
- ▶ Metalclad all supplied with metal back boxes
- ▶ 1 year guarantee



M22SW

Please see page 2 for Fused Connection Units

### TECHNICAL INFO

Product	M22W	M22M	M22SW	M22SM
<b>Description</b>	RCD Unswitched Socket		RCD Switched Socket	
<b>Barcode</b>	5012739 608704	5012739 608711	5012739 641510	5012739 641534
<b>Product Finish</b>	White	Metalclad	White	Metalclad
<b>Product Weight</b>	230g	510g	231g	507g
<b>Product Dimensions</b>	H86.5 X W147 x D35mm (16mm surface projection)	H86.5 X W147 x D50mm	H86.5 X W147 x D35mm (16mm surface projection)	H86.5 X W147 x D50mm
<b>Voltage</b>	230V AC ~ 50Hz			
<b>Max Operating Current</b>	Resistive Load: 13A Inductive Load: 13A			
<b>IP Rating</b>	IP20			
<b>Rated Trip Current</b>	30mA			
<b>Typical Trip Speed</b>	<40mS			
<b>RCD Contact Break</b>	Double Pole			
<b>Latching</b>	Mechanically latched - no need to reset after power loss			
<b>Terminal Capacities</b>	Upto 3 x 1.5mm <sup>2</sup> / 3 x 2.5mm <sup>2</sup>			
<b>Main Housing Material</b>				
<b>Guarantee</b>	1 Year			
<b>Conforms to</b>	BS 7288:2016+A1:2022 & BS 1363-2:2023			

### FEATURES

- ▶ Type A RCD
- ▶ Mechanical flag trip indicators
- ▶ Mechanically latched - no need to reset after power loss
- ▶ All products have separate 'Test' & 'Reset' buttons
- ▶ Metalclad all supplied with metal back boxes
- ▶ 1 year guarantee



M92W



M92M

### TECHNICAL INFO

Product	M92W	M92M
<b>Description</b>	RCD Fused Connection Unit	
<b>Barcode</b>	5012739 608728	5012739 608735
<b>Product Finish</b>	White	Metalclad
<b>Product Weight</b>	162g	351g
<b>Product Dimensions</b>	H86.5 X W86.5 x D37mm (16mm surface projection)	H87 X W87 x D50mm (Inc back box)
<b>Voltage</b>	230V AC ~ 50Hz	
<b>Max Operating Current</b>	Resistive Load: 13A Inductive Load: 13A	
<b>IP Rating</b>	IP20	
<b>Rated Trip Current</b>	30mA	
<b>Typical Trip Speed</b>	<40mS	
<b>RCD Contact Break</b>	Double Pole	
<b>Latching</b>	Mechanically latched - no need to reset after power loss	
<b>Terminal Capacities</b>	Upto 3 x 1.5mm <sup>2</sup> / 3 x 2.5mm <sup>2</sup>	
<b>Main Housing Material</b>		
<b>Guarantee</b>	1 Year	
<b>Conforms to</b>	BS 7288:2016+A1:2022 & BS 1363-4:2023	