

IP65 3.5W LED EMERGENCY BULKHEAD - MAINTAINED/NON-MAINTAINED

Cost effective emergency luminaire for interior and exterior applications. This bulkhead can be wall or ceiling mounted.

- Polycarbonate body & diffuser
- Hinged gear tray
- Facility for remote switching
- Built in battery protection & charge indicator
- Emergency operation duration 3 hours
- Link changeable to maintained/non-maintained



ELBHLEDEN

Product Finish	White/Clear
Description	LED Bulkhead Unit
Wattage	3.5W
Product Dimensions	H55 x W110 x L352mm
Product weight	532g
Barcode	5012739642883
IP Rating	IP65
Lamp Type	LED Non-replaceable
Class Type	Class 1
Knock Outs	16mm
Charge Time	24 hours
Operating Temp Range	0°C - 40°C
Colour Temp	6500K
Lumen Output	Maintained 160 lm Battery 145lm
Maintained/Non-Maintained	Link changeable
Battery Type	Ni-Cd 3.6V / 1500mAh
Voltage	230V/240V AC ~ 50Hz
Main housing material	Polycarbonate body & diffuser
Guarantee	3 Years
Certification & Conformity	BS EN 60598-2-22

TECHNICAL DATA SHEET



Complete with vinyl self adhesive Legends - Arrow down, Arrow Up, Arrow Right & Arrow Left