

INSTALLATION / OPERATING INSTRUCTIONS FOR DUAL VOLTAGE SHAVER SOCKET

MODEL NUMBER: HS1

SAFETY INSTRUCTIONS

- This product should be installed by a qualified electrician in accordance with these instructions and the current IEE regulations.
 This product must be earthed.
- This product must be earthed.
 All bare earth wires must be covered with the appropriate green/yellow

sleeving, not supplied. Ensure all

electrical connections are tight.

4. Please check with manufacturers instructions for suitability with rechargeable shavers.

INSTALLATION & WIRING INSTRUCTIONS

- Ensure power supply is disconnected before proceeding with the installation.
 Shaver socket should be mounted in
- a 47mm back box.Feed the supply cable through the appropriate knockout in the
 - installation box. If using a metal back box you will need to fit a 20mm rubber grommet.
- Strip outer sheath of the supply cable to suitable length and then remove 10mm of the insulation from the Live (brown or red) and Neutral (blue or black) conductors to expose the inner cores.
- 5. Insert Neutral (blue or black)
 conductor into the terminal
 marked N and fully tighten screw.
 6. Insert Live (brown or red) conductor
- Insert Live (brown or red) conductor into the terminal marked L and fully tighten the screw.
 Insert the earth conductor,
- Insert the earth conductor, ensuring it has been sleeved with green/yellow sleeving, into the terminal marked
- Ensure that an additional earth cable is connected between the shaver supply unit earth terminal and the earth terminal in the back box being used.
- Fit socket to back box with the two fixing screws provided.
- 10. Reconnect supply.

To select the voltage required 115V/230V by inserting shaver plug into the appropriate socket.

Always unplug appliance after use.

SPECIFICATION

115/230VA - 20VA Max Load

GUARANTEE

Your KingSheild Dual Voltage Shaver Socket is guaranteed for 12 months from the date of purchase. This does not affect your statutory rights.

PLEASE KEEP THESE INSTRUCTIONS SAFE FOR FUTURE REFERENCE



