

-PowerBreaker-

Mains Isolator Switch - Information Sheet

The PowerBreaker range of circuit protection devices are designed and tested for use with PowerBreaker Consumer Units.


These devices **MUST** be installed and tested by a qualified electrician in accordance with the latest Wiring Regulations (BS7671).

PBI - Mains Isolator Switch

The Mains Isolator Switch isolates the Live & Neutral to the consumer unit.



Torque Setting & Cable Strip Length



TECHNICAL INFORMATION

	PBI
Rated Residual Current	100A
Pack Quantity	6
Barcode	5012739 648526
Number of Poles	2P (Double Pole)
Rated Voltage	230/240VAC
Rated Frequency	50/60Hz
Terminals	1 -35mm ²
Mechanical Endurance	10,000 times
Electrical Endurance	4,000 times
Ambient Temperature	- 25°C to +55°C
Storage Temperature	- 40°C to +70°C
Torque (Rec minimum required)	2.5Nm
Din Rail Mounting	Yes
Guarantee	3 Years
Conforms To	BS EN 60947

*Please keep this information
for future reference*

**GREEN
BROOK**
ELECTRICAL
WEST ROAD . HARLOW
ESSEX . CM20 2BG . UK
info@greenbrook.co.uk
www.greenbrook.co.uk

GUARANTEE
Your PowerBreaker Mains Isolator Switch
is guaranteed for 3 years from
the date of purchase.
This is in addition to your statutory rights

