

TWIN SPOTS - NON-MAINTAINED

Powerful Twin Spot Non-Maintained fittings for defined escape routes in interior (ELTSLED20NM) and exterior (ELTSLED65NM) applications. Ideal for use in warehouses, factories, long corridors and high bay industrial applications.

- Adjustable heads
- Individual LED lamp health indicators
- Emergency operation duration 3 hours
- Fused main terminals



ELTSLED65NM



ELTSLED20NM

| | ELTSLED65NM | ELTSLED20NM |
|---------------------------------------|----------------------------------|-------------------------|
| Product Finish | White | White |
| Description | LED Twin Spot | LED Twin Spot |
| Wattage | 5.4W Total | 5.2W |
| IP Rating | IP65 | IP20 |
| Product Dimensions | H290 x W300 x D70mm | H308.5 x W280 x D55.5mm |
| Product Weight | 1630g | 1143g |
| Barcode | 5012739633898 | 5012739638343 |
| Lumens Output (Emergency mode) | Battery - 590 lm | Battery - 385 lm |
| Battery Type | 3.6V/6Ah Ni-Cd | 3.6V 4.5Ah Ni-Cd |
| Voltage | 230V AC ~ 50Hz | |
| Main Housing Material | Polycarbonate body | |
| Charge Time | 24 hours | |
| Guarantee | 3 Years | |
| Certification & Conformity | BS EN 60598-1 / BS EN 60598-2-22 | |